

FSR-200 LIVIANA T: Bandas cortas Tolerancia Peso + /- 2%



200	200	1085	10.00R
200T	200	1075	8.15/75R17 / 9.00R20
215	215	1085	9.00R / 11R / 12R
215 T	215	1088	8.45 70 / 275
220	220	1085	10.00R / 11.00R / 11R / 12R
220 T	220	1087	10.00 / 11R / 275
225	225	1088	10.00R / 11.00R / 11R / 12R
225 T	225	1080	10.00R / 11R / 275
232	232	1015	10.00R / 11R / 12.00R / 12R
232 T	232	1088	8.55 70 / 275 / 295
240	240	1015	10.00R / 12.00R / 12R
240 T	240	1015	10.00R / 12R / 13R
250	250	1015	10.00R / 295
250 T	250	1015	10.00 / 295 / 315

PRESTACIONES

USOS

- > Camiones o autobuses de uso regional o larga distancia

RECOMENDACIONES

- > as

VELOCIDADES

- > Uso en ejes direccionales

GARANTÍAS

Dimensión	[Telas]	Índice de carga [IC]	Índice de velocidad [IV]	Capacidad de carga máxima [KG]	Llanta Recomendada	Neumático nuevo		Máximo de Servicio		
						Ancho de sección +/- 4% mm	Diámetro total +/- 1.5% mm	Ancho total mm	Diámetro total mm	Presión de carga máxima